

1 Phase Servo Stabilizer

Better Voltage Protection



Application :

- House / Solar
- Office
- Bungalow
- Farm house
- Machinery
- Industries
- Lift / Elevator



Technical Specification

• INPUT VOLTAGE RANGE	170-270 v / 150-300 v
• OUTPUT VOLTAGE RANGE	230 V
• OPERATING FREQUENCY	47-53 HZ
• OUTPUT REGULATION	1%
• RATE OF CURRETION	60 V/SEC
• WAVE FORM DISTROCTION	NILL
• EFFICIENCY	98%
• RESPONCE TIME	10 M SEC.
• IS STANDARD	IS 9815
• TERMINATION	CONNECTOR
• COOLING TYPE	AIR COOL
• CONTROLLER TYPE	DIGITAL MICRO PROCESSOR CONTROL CARD
• CONNECTION WIRE	P + N + E
• PROTECTIONS	HIGH VOLTAGE CUTOFF LOW VOLTAGE CUTOFF OVERLOAD CUTOFF SHORT CIRCUIT PROTECTION BY MCB

Rameshwar Power Control

+91 98248 12053 / 88666 65036

rameshwar.electricals@yahoo.com

www.rameshwarstabilizer.com

MARUTI IND. AREA, PLOT NO. 3&4, SHED NO. 4, NR.PGVCL
OFFICE, VAVDI, RAJKOT-360004, GUJARAT-INDIA.